Australasian Health Facility Guidelines

Room Data Sheet





Bay - Scrub

Room Code	B-SCRUB
Briefed Area	4.00 m²
Ceiling Height	2.7 m
Occupancy	Up to 3 staff
Hours of Operation	Up to 24 hours

Description

The Bay - Scrub room provides an area and facilities for performing surgical hand antisepsis prior to entering the Operating Room and donning sterile gloves and gowns. Surgical hand antisepsis is performed to substantially reduce the number of micro-organisms on the hands prior to performing any aseptic or surgical procedure.

Electrical	PROTECTION: body protected		HVAC	AIRCONDITIONING: general	4		
	PROTECTION: cardiac protected			AIRCONDITIONING: HEPA filtered			
Lighting	LIGHTING: general	1		AIRCONDITIONING: positive pressure			
gg	LIGHTING: colour corrected	_		AIRCONDITIONING: negative pressure			
	LIGHTING: dimmable			VENTILATION: exhaust			
	LIGHTING: indirect			VENTILATION: supply			
				VENTILATION: natural			
Nurse Call and Duress	NURSE CALL SYSTEM: buttons / handset		Medical Gas	MEDICAL GAS: general anaesthesia			
Duless	NURSE CALL SYSTEM: annunciator		moulour out	MEDICAL GAS: special care			
	DURESS: fixed			MEDICAL GAS: special care, neonatal ventilation			
	DURESS: wireless coverage			MEDICAL GAS: birthing			
Security	ACCESS CONTROL: to door			· ·	_		
_	ACCESS CONTROL: to item / joinery		Hydraulic	WATER: drinking	1		
	INTERCOM: service communications			WATER: specialty			
	INTERCOM: security and access control			DRAINAGE: sanitary			
	CCTV: camera coverage within room			DRAINAGE: specialty			
	INTRUSION DETECTION: door monitoring		Fire	DETECTION: smoke	4		
	INTRUSION DETECTION: spatial monitoring			DETECTION: heat			
ICT and Audio	AUDIO VISUAL: patient entertainment system		Shielding	SHIELDING: ionising radiation			
Visual	AUDIO VISUAL: visitor experiance system			SHIELDING: magentic and radio frequency			
	AUDIO VISUAL: virtual collaboration system		Acoustics	SPEECH PRIVACY:			
	AUDIO VISUAL: clinical support system		7100001100	not private ······ moderate ······ private ····· confide	ontial		
	AUDIO VISUAL: digital operating room system			NOISE SENSITIVITY:	ziillai		
Accessibility	AUDIO: hearing augmentation			not sensitivesens	eitive		
•	VISUAL: luminance contrast			NOISE GENERATION:	Silive		
	SIGNAGE: accessible, statuatory			▼			
	•	_		low moderate high very	nigh		

Additional Considerations

- Number of taps and soap/hand-rub dispensers to be confirmed to suit staffing and service requirements.
- A minimum of 900mm is required between taps to allow for sufficient space for taps to be used simultaneously.
- Taps to be non-touch, either operated with sensor activation or elbow levers.
- Provision of a shelf above the scrub trough to be confirmed at project level to suit service requirements (considering provision of dispensers/holders, cleaning protocols and mounting height provision to suit workplace health and safety policies).
- Height and type of wall finish to suit local infection prevention and control policies and rigorous cleaning regimes. Provision and height of corner guards as required to provide protection from anticipated mobile equipment movement.
- Depending on proximity of this room to the Operating room and the use of x-ray equipment during procedures, radiation shielding may be required to some walls of this room and is to be assessed by a Radiation Consultant.

Issue date: 06.05.2025

Revision: 2

Copyright © 2025 Australasian Health Infrastructure Alliance (AHIA)

Room code: B-SCRUB



CODE	DESCRIPTION	COMMENT
FLVY-111	FLOOR FINISH: vinyl, seamless, non-slip	minimum slip rating R10 / pendulum P3 or agreed equivalent
FLSK-021	SKIRTING: vinyl, integral with floor vinyl, coved	
WLFI-011.07	WALL FINISH: vinyl, full height	
WLPR-006.07	WALL PROTECTION: corner guards, full height	
CLFS-011	CEILING: flush set, suspended	
CLFI-002	CEILING FINISH: paint, clinical areas	
CLCN-031	CORNICE: square set	



Joinery

CODE	DESCRIPTION	GROUP	QTY	COMMENT
JOSH-402	SHELF: wall mounted, stainless steel	1	1	optional; mounted above scrub trough



Fittings, Furniture and Equipment (FF&E)

CODE	DESCRIPTION	GROUP	QTY	COMMENT
FIBM-102	MIRROR: fixed, safety glass, frameless	0	1	900H x 450W, at 900H AFFL
FIDI-101	DISPENSER: PPE, disposable masks, wall mounted	2	1	
FIDI-106	DISPENSER: PPE, disposable gloves, wall mounted	2	1	for non-sterile gloves
FIDI-131	HOLDER: PPE, goggles, wall mounted	2	1	
FIDI-201	DISPENSER: scrub brush, wall mounted	2	1	
FIDI-231	DISPENSER: paper towel, wall mounted	2	1	
FIDI-251	DISPENSER: alcohol-based hand rub, surgical, antimicrobial, chlorhexidine, wall mounted	2	1	
FIDI-256	DISPENSER: soap, wall mounted	2	1	
FIDI-266.01	DISPENSER: hand wash, surgical, antimicrobial, chlorhexidine, wall mounted	2	1	
FIDI-266.02	DISPENSER: hand wash, surgical, antimicrobial, povidone-iodine (PVI), wall mounted	2	1	
FIDI-271	DISPENSER: moisturiser, wall mounted	2	1	
FQWS-051	BIN: general waste, 20L	3	1	size, type and quantity of bins will be dependent on local waste management policies for waste separation
HYBA-112	SCRUB TROUGH: type A, handwashing, floor mounted	0	1	
HYTP-121	TAPWARE: scrub trough, sensor tap and plate, trough mounted	0	1	
ITCL-067	CLOCK: electric, master clock system, slave, digital	1	1	to be mounted flush to wall



Engineering Services

(CODE	DESCRIPTION	GROUP	QTY	COMMENT
	HYTP-453	DIRECT CONNECTION: water, warm	0	3	to sensor tap spouts

Issue date: 06.05.2025

Revision: 2

Page: 2 of 3 Room code: B-SCRUB

Issue date: 06.05.2025 Revision: 2

Page: 3 of 3
Room code: B-SCRUB