



## Bay - Beverage

<b>Room Code</b>	BBEV
<b>Briefed Area</b>	4.00 m <sup>2</sup>
<b>Ceiling Height</b>	2.7 m
<b>Occupancy</b>	1-2 persons intermittently
<b>Hours of Operation</b>	Up to 24 hours (dependent on unit operating hours)

**Description** | The Beverage Bay is an area for preparation (including heating as required) of refreshments, snacks and small meals, washing some utensils, storing small mounts of food and drink and disposing of food waste (in accordance with food hygiene requirements).

**Electrical**

PROTECTION: body protected	<input type="checkbox"/>
PROTECTION: cardiac protected	<input type="checkbox"/>

**HVAC**

AIRCONDITIONING: general	<input checked="" type="checkbox"/>
AIRCONDITIONING: HEPA filtered	<input type="checkbox"/>
AIRCONDITIONING: positive pressure	<input type="checkbox"/>
AIRCONDITIONING: negative pressure	<input type="checkbox"/>
VENTILATION: exhaust	<input type="checkbox"/>
VENTILATION: natural	<input type="checkbox"/>

**Lighting**

LIGHTING: general	<input checked="" type="checkbox"/>
LIGHTING: colour corrected	<input type="checkbox"/>
LIGHTING: dimmable	<input type="checkbox"/>
LIGHTING: indirect	<input type="checkbox"/>

**Nurse Call and Duress**

NURSE CALL SYSTEM: buttons / handset	<input type="checkbox"/>
--------------------------------------	--------------------------

### Additional Considerations

- Beverage bays may allocated to patient care areas, staff areas and meeting/education facilities.
- Ready access to a handwashing basin is recommended.
- If an instantaneous boiling water tap/unit is provided, it should be hardwired and access restricted to the unit e.g. within cupboard. If system is located within a joinery unit, ensure appropriate ventilation is provided.
- A side approach to the sink for wheelchair access has been shown; front access may be required depending on local/jurisdictional policies and service requirements.
- The Beverage Bay should be adequately recessed to avoid encroachment into the corridor. If the space is to be enclosed and/or access is restricted, an increase in area is required. The door will require an observation panel.
- Size, type and quantity of waste bins is dependent on environmental management policies and service requirements. Where a facility has additional waste streams, beyond the general waste and comingled recycling indicatively shown in this Standard Component, additional area may be required to accommodate the receptacles. Depending on frequency of waste removal, bin sizes may be larger in high use areas or as guided by local waste management policies. Joinery to conceal bins may be provided depending on infection prevention and control policies.
- Fridge dimensions will vary depending on selection and service requirements; clear area provided for the fridge is to allow for adequate ventilation and full opening of door
- Provision and type of ice machine will be dependent on service requirements and local infection prevention and control policies.



## Finishes

CODE	DESCRIPTION	COMMENT
FLVY-101	FLOOR FINISH: vinyl, seamless, standard slip resistance	[FLVY-007] floor finish must be minimum slip rating R10/pendulum P3 or agreed equivalent around sink; coordinated with adjacent area, significant change in colour to be avoided
FLSK-021	SKIRTING: vinyl, integral with floor vinyl, coved	[FLSK-010] to be coordinated with adjacent area
WLFI-001	WALL FINISH: paint	[WLWA-004]

CODE	DESCRIPTION	COMMENT
WLFI-101	SPLASHBACK: vinyl	[WLWA-007] to back of bench and return wall
CLTI-022.02	CEILING: drop-in tiles, acoustic, prefinished, 600 x 1200	[CLTI-002] to be coordinated with adjacent area
CLCN-041	CORNICE: wall trim fixing, prefinished	[CLCN-009] to be coordinated with adjacent area
WLPR-006.01	WALL PROTECTION: corner guards, to 900 AFFL	[WLPR-010] coordinated with adjacent wall protection



## Joinery

CODE	DESCRIPTION	GROUP	QTY	COMMENT
JOBE-061	BENCH: 750D, laminate	①	1	[FIJO-069] minimum depth 600mm; where an ice machine is provided the depth may need to increase to accommodate
JOCU-041	CUPBOARD: tall, with 1 microwave shelf unit	①	1	[FIJO-163]
JOCU-121	CUPBOARD: wall mounted, double door	①	1	[FIJO-143] optional; configuration of joinery to meet storage requirements
JOCU-221	CUPBOARD: under bench, double door	①	1	[FIJO-135]
JODW-031	DRAWER UNIT: under bench, 3 drawers, equal	①	2	[FIJO-104]
JOGE-001	BULKHEAD: joinery	①	1	[FIJO-212] optional, provide if wall mounted joinery provided, plasterboard bulkhead is also acceptable
JOGE-001	BULKHEAD: joinery	①	1	[FIJO-212] plasterboard bulkhead is also acceptable



## Fittings, Furniture and Equipment (FF&E)

CODE	DESCRIPTION	GROUP	QTY	COMMENT
FQCA-101	APPLIANCE: microwave, benchtop, domestic	③	1	[FQCA-067]
FQCA-231	ICE MACHINE: commercial, benchtop	③	1	[FQCA-015] optional; item to comply with infection control requirements
FQCA-402	FRIDGE: domestic, 300L nom, single door	③	1	[FQCA-032] clear area for fridge to allow for adequate ventilation and full opening of door
FQWS-053	BIN: general waste, 50L	③	1	[FQCW-019] size, type and quantity of bins dependent on local waste management policies
FQWS-073	BIN: recycling, commingled, 50L	③	1	[FQCW-062] size, type and quantity of bins dependent on local waste management policies
HYBA-304	SINK: single bowl, with drainer, accessible	①	1	[HYBA-080]
HYGE-111	WATER SYSTEM: filter unit and tap, boiling/chilled	①	1	[HYGE-003] + [HYTP-029] instant hot/cold water tap to sink; provide grille in joinery for ventilation
HYTP-152	TAPWARE: sink, mixer, fixture mounted, accessible	①	1	[HYTP-040]



## Engineering Services

CODE	DESCRIPTION	GROUP	QTY	COMMENT
ELGP-101	GPO: single, wall mounted	①	3	[ELGP-109] 1 to fridge, 1 to microwave, 1 to boiling/ chilled water unit
ELGP-201	GPO: double, wall mounted	①	2	[ELGP-208] over bench

CODE	DESCRIPTION	GROUP	QTY	COMMENT
ELSW-001	SWITCH: light	①	1	[ELBO-015] optional, lighting and controls to be coordinated with adjacent area
HYDR-201	DIRECT CONNECTION: wastewater, general	①	1	to sink
HYTP-431	OUTLET: water, cold	①	1	[HYTP-008] to boiling/ chilled water unit
HYTP-451	DIRECT CONNECTION: water, cold	①	1	to sink tapware
HYTP-452	DIRECT CONNECTION: water, hot	①	1	to sink tapware

For guidance on how to use the Room Data Sheet, please visit the [AusHFG website](#).