Standard Components - Room Data Sheet

Room Name	Bay - Public Telephone

Room Number: BPH

Last modified	01/03/2016
Briefed Area	2.00
Remarks	
Occupancy	*1 - 2*
Hours of Operation	☑ *24 Hours*
Acoustics	
Description / Special Requirements	*A bay with provision for public telephones; Access should be provided for persons with disabilities.The Public Telephone Bay should be located where justified, such as, Main Entry and Emergency Department. Security considerations:- Fixed to wall to prevent theft/tampering. Design considerations:- A 2m2 bay will accommodate one (1) public telephone and a taxi phone. Add 1m2 per additional telephone.- A bay is shown, however, wall mounted in a corridor may be an alternate approach.*

Room Fabrics

AusHFG code	Description	Material	Finish	Specification	Comments
1000	Floor finish	Vinyl	Standard slip resistant	Seamless, coved	Default = vinyl: or consitent with adjacent space
3000	Wall finish	Paint	Acrylic, washable		
2670	Wall protection			Corner guards to 900 AFFL minimum	Align heights of corner guards with other corridor elements
2709	Ceiling	Acoustic	Prefinished	Drop-in tiles	Or consistent with adjacent space.
6030	Cornice	Aluminium	Powdercoat	24mm shadow angle	
2000	Skirting	Vinyl	Prefinished	Floor vinyl coved, 150 mmH	Default = vinyl: or consitent with adjacent space

Fittings and Furniture

AusHFG code	Description	Group	Qty	Comments
FF-1050	Bench - laminate	1	2	1 at disabled access height.
FF-16840	Partitions - laminate	1	1	Between telephones bays. Quantity to suit number of bays.

Fixtures, Equipment and associated Services

AusHFG code	Description	Grp	Qty	Ele	Data	CdW	HtW	WmW	Tap	Dns	Gas	Comments
FE-41900	Telephone - public	3	1	☑	☑	☐	☐	☐	☐	☐	☐	Add an additional public telephone if taxi phone not required.
FE-6189	Telephone - taxi	3	1	☑	☑	☐	☐	☐	☐	☐	☐	Optional. Locate at main entry point to Hospital and/ or Ambulatory Care. If not required add another public telephone.

Service Requirements

Room Name | **Bay - Public Telephone**   **Room Number: BPH**

AusHFG code	Description	Comments
S-5000	Airconditioning	
S-6000	General fluorescent	

Services

AusHFG code	Description	Group	Qty	Comments
S-1005	Voice / Data outlet: single	1	2	in ceiling for data projector; optional
S-5000	Airconditioning	1	1	
S-6000	General fluorescent	1	1	
S-1983	General fluoresecent downlights	1	2	