

Standard Components - Room Data Sheet

Room Name | Bay - Storage, 4m2 Room Number: BS-4

Last modified 01/03/2016

Briefed Area Remarks Occupancy Hours of Operation 4.00

s of Operation

☑ Available 24 Hours

Acoustics
Description or Special
Requirements

An open storage bay located adjacent to patient treatment areas for holding of supplies in frequent use. Stock will be stored in open, heavy duty, adjustable shelving units. Special Design Requirements: - The Bay should not impede corridor circulation

Room Fabrics

AusHFG code	Description	Material	Finish	Specification	Comments
1000	Floor finish	Vinyl	Standard slip resistant	Seamless, coved	or consistent with adjacent area
3000	Wall finish	Paint	Acrylic, washable		
4031	Wall protection	Composite	Prefinished PVC	Corner guards to 1500 AFFL	Equal to 'Acrovyn'
5010	Ceiling - Plasterboard	Plasterboard	Paint, washable	Flush set, suspended	or consistent with adjacent area
6030	Cornice	Aluminium	Powdercoat	24mm shadow angle	or consistent with adjacent area
2000	Skirting	Vinyl	Prefinished	Floor vinyl coved, 150 mmH	or consistent with adjacent area

Fittings and Furniture

AusHFG code	Description	Group	Qty	Comments
FF-13660	Metal shelving - 900x400x2100	3	4	heavy duty

Fixtures, Equipment and associated Services

Service Requirements

AusHFG code	Description	Comments
S-5000	Airconditioning	
S-6000	General fluorescent	

Services

AusHFG code	Description	Group	Qty	Comments
S-5000	Airconditioning	1	1	
S-6000	General fluorescent	1	1	



