

Standard Components - Room Data Sheet

Room Name | Bay - Wheelchair Park, 4m2 Room Number: BWC

Last modified

01/03/2016

Briefed Area Remarks Occupancy

4.00

Hours of Operation

☑ 24 Hours

Acoustics
Description or Special
Requirements

An open storage bay for wheelchairs, located in close proximity to the main entrance. Special Design Requirements: The Bay should be deep enough to ensure equipment stored does not impede corridor circulation; minimum depth 1200mm.

Room Fabrics

AusHFG code	Description	Material	Finish	Specification	Comments
1000	Floor finish	Vinyl	Standard slip resistant	Seamless, coved	consistent with adjacent area
3000	Wall finish	Paint	Acrylic, washable		
4020	Wall protection	Composite	Prefinished PVC	Crash rail at 900 AFFL	Equal to 'Acrovyn'
4031	Wall protection	Composite	Prefinished PVC	Corner guards to 1500 AFFL	Equal to 'Acrovyn'
4022	Wall protection	Composite	Prefinished PVC	Crash rail at 350 AFFL	Equal to 'Acrovyn'
5010	Ceiling - Plasterboard	Plasterboard	Paint, washable	Flush set, suspended	consistent with adjacent area
6030	Cornice	Aluminium	Powdercoat	24mm shadow angle	consistent with adjacent area
2000	Skirting	Vinyl	Prefinished	Floor vinyl coved, 150 mmH	consistent with adjacent area

Fittings and Furniture

AusHFG code	Description	Group	Qty	Comments
FF-24200	Wheelchair	3	3	as required

Fixtures, Equipment and associated Services

Service Requirements

AusHFG code	Description	Comments
S-5000	Airconditioning	
S-6000	General fluorescent	

Services

AusHFG code	Description	Group	Qty	Comments
S-9001	GPO: Double	1	1	
S-5000	Airconditioning	1	1	
S-6000	General fluorescent	1	1	



