

Standard Components - Room Data Sheet

Office - Shared Workstation, 2.2m2 **Room Number: OFF-SWS Room Name** Last modified 01/03/2016 **Briefed Area** Remarks Occupancy 1 staff member or visitor **Hours of Operation** ✓ 8am to 6pm, daily **Acoustics Description / Special** Requirements A workstation within an open plan arrangement for multiple users to share a workbase during different time periods to carry out administrative/data entry functions. It may also be appropriate for roving staff who are not at their workstation for long periods of time on a daily basis. Consider small meeting table between workstations in high density areas.

Room Fabrics

AusHFG code	Description	Material	Finish	Specification	Comments	
1130	Floor finish	Carpet	90/10 Wool/ Nylon	Carpet tiles	Or vinyl	
3000	Wall finish	Paint	Acrylic, washable			
5060	Ceiling - Acoustic	Acoustic	Prefinished	Drop-in tiles, 600x1200		
6030	Cornice	Aluminium	Powdercoat	24mm shadow angle		
2010	Skirting	Vinyl	Prefinished	Feather edged, 150 mmH	Coved vinyl to vinyl flooring	

Fittings and Furniture

AusHFG code	Description	Group	Qty	Comments
FF-1050	Bench - laminate	1	1	Seated height. Length to suit layout, refer RLS or project specific requirements.
FF-2100	Chair - ergonomic, office	3	1	
FF-5824	Waste bin - general	3	1	

Fixtures, Equipment and associated Services

AusHFG code	Description	Grp	Qty	Ele	Data	CdW	HtW	WmW	Тар	Dns	Gas	Comments
FE-11400	Computer - PC & monitor	3	1	V	V							Consider location of harddrive, if below desk add bracket.
FE-54510	Telephone - handset, standard	3	1		V							1 shared between 2 workspaces optional.

Service Requirements

AusHFG code	Description	Comments
S-5000	Airconditioning	
S-6000	General fluorescent	

Services

AusHFG code	Description	Group	Qty	Comments
S-9001	GPO: Double	1	2	







Standard Components - Room Data Sheet

Room Name Office - Shared Workstation, 2.2m2 Room Number: OFF-SWS

AusHFG code	Description	Group	Qty	Comments
S-1006	Voice / Data outlet: double	1	1	1 outlet for telephone
S-5000	Airconditioning	1	1	
S-6000	General fluorescent	1	1	



