



Room Name	1 Bed Room - Mental Health - Inboa	ard E	nsuite, 15m2 Room Number 1BR-MH-A	
Revision	5			
Issue Date	02.07.2018			
BRIEFING				
Briefed Area	15.00 m ²			
Hours of Operation	24 Hours			
Occupancy	1 patient; 1-2 staff; 1-2 visitors			
Acoustics	Acoustic privacy is required			
Remarks				
Description / Special Requirements	internally lockable with a master keyed lockable with a building must be of a type manufactur manufacturer's instructions. Door and join ligature points and must be tamper proof. 15kg (e.g. clothes hooks). All glazing (incl AS/NZS 2208 and AS 1288, specifically, to requivalent approved. The 1 Bed Room options, including inboard and back to bat that a portable call and duress device is p	ck from ed and ery had Select luding cougher - Mer ck. Starovide	ents. Natural light and outlook is essential. The room is to be the outside. All fittings and fixtures used in consumer are domarketed as anti-ligature; and installed in accordance with airdware and any engineering services outlets must not provided fixtures are to have a breaking strain of not more than external windows) is to be Grade A safety glass to comply ened laminated glass with a minimum thickness of 14.28mm hall Health may vary in configuration to suit different Ensuite aff to staff nurse call has not been provided on the assumpted to staff. Consider location of wi-fi access points to ensure ess functions. Jurisdictional policy to be read in conjunction	as of th the vide with m, e tion
SERVICES				
General Requirements	BODY PROTECTED	\checkmark	CARDIAC PROTECTED	
Air	AIRCONDITIONING	V	AIRCONDITIONING: hepa filtered	
All	AIRCONDITIONING AIRCONDITIONING: positive pressure		AIRCONDITIONING: hepa linered AIRCONDITIONING: negative pressure	
	EXHAUST: room exhaust		VENTILATION	
Lighting	LIGHTING: colour corrected		LIGHTING: dimmable	
	LIGHTING: downlights		LIGHTING: downlights, dimmable	
	LIGHTING: fluorescent/LED, downlights		LIGHTING: fluorescent/LED, flush with ceiling, tamper proof	V
	LIGHTING: fluorescent/LED, general		LIGHTING: indirect	
Nurse Call	NURSE CALL SYSTEM	V		

Room Fabrics

AusHFG code	Description	Comment	
CLFS-006	CEILING: plasterboard, flush set, suspended, paint, washable	for High Dependency and intensive care areas, consider plywood or equivalent backing to ceiling finish	
CLCN-008	CORNICE: square set flush between wall and ceiling, paint		
DWGL-074	DOOR: 1120mm c/o, 1 1/2 leaf in/out opening, observation panel, solid core/safety glass, paint	lockable, anti ligature door hardware	
FLVY-002	FLOOR FINISH: vinyl, seamless, coved, cushioned		
FLSK-010	SKIRTING: vinyl, floor vinyl coved, 150H, prefinished		
WLWA-003	WALL FINISH: laminated composite board	to back of ensuite door	
WLWA-004	WALL FINISH: paint, acrylic, washable		
WLPR-002	WALL PROTECTION: bed protection wall panel, composite, laminate finish		
DWWH-005	WINDOW	natural light and outlook essential	

ALHA

averages to the first schere ellipse

considered to a section of the sectio



Room Name

1 Bed Room - Mental Health - Inboard Ensuite, 15m2 Room Number 1BR-MH-A

Fittings, Furniture and Equipment (FF&E) Items

AusHFG code	Description	Group	Qty	Comment
MMBE-017	BED: patient, mental health, electric	3	1	or mattress on built-in plinth
FIJO-210	BEDHEAD: mental health	1	1	
DWWD-007	BLIND: venetian, integral	1	2	to window/s, obs panel in door
FIJO-212	BULKHEAD: joinery	1	1	
FQBS-056	CHAIR: tub, mental health	3	1	
FIJO-215	CUPBOARD: tall, shelf unit, fixed shelves, anti-ligature, 500D	1	1	
FQDW-025	DESK: built in, return end, anti ligature	1	1	laminate finish
FIBM-022	MIRROR: fixed, safety glass, toughened and laminated, anti ligature	1	1	optional, glued to backing material and screw fixed
FIBM-015	NOTICEBOARD: fixed, velcro	2	1	
FQSN-062	SAFE: small	1	1	optional, for patient belongings, suitable for mental health environments, bolt into place
FQBS-054	STOOL: ottoman	3	1	suitable for mental health environments
FQTA-083	TABLE: bedside, anti ligature	3	1	unit is weighted, optional choice of tamper proof wheels or sliders for mobility. Fixed unit is optional alternative

Engineering Services

AusHFG code	Description	Group	Qty	Comment
ITCL-006	BUTTON: nurse call, patient to staff	1	1	optional depending on client age group and jurisdicational policy; mobile duress preferred; + indicator button & light
ELGP-208	GPO: double, wall mounted	1	1	to desk
ELGP-109	GPO: single, wall mounted	1	2	
ELGP-110	GPO: single, wall mounted, cleaner	1	1	optional
LIFX-001	LIGHT: night light, tamper proof, anti ligature	1	1	recommended to be on emergency power
LIFX-034	LIGHT: reading light, tamper proof, anti ligature, ceiling recessed	1	1	can also be wall recessed
ITSE-045	SENSOR: motion detection, for lighting control, flush to ceiling	1	1	optional
ITSE-047	SENSOR: motion detection, for staff alert, flush to ceiling	1	1	
ELBO-015	SWITCH: light, single	1	3	plus two located outside door for light and night light; lighting to have controlled switching to create low stimulus environment. one may optionally be replaced with light motion sensor deactivation switch

AHHA

Page: 2 Print Date: 03/07/2018