

| Room Name | Airlock - Entry, 6m2 | Room Number AIRLE-6 | | | |
|---------------------------------------|---|--|--|--|--|
| Revision | 5 | | | | |
| Issue Date | 20.03.17 | | | | |
| BRIEFING | | | | | |
| Briefed Area | 6.00 m ² | | | | |
| Hours of Operation | 24 Hours | | | | |
| Occupancy | 24 110013 | | | | |
| Acoustics | | | | | |
| Remarks | | | | | |
| Description / Special Requirements | Airlock associated with a Main Entry Area for wind/ weather protection and to maintain air pressurisation. It will be used by a wide range of people including fully ambulant, persons using a wide range of walking aids, persons in wheelchairs or on trolleys and the general public. The size of the air lock should allow for several people to enter before the second door opens and should reflect the level of service provision. Entry doors may be glazed and automatic. Walls may also be glazed. After-hours access may require intercom or special security provisions. | | | | |
| SERVICES | | | | | |
| General Requirements | BODY PROTECTED = No | CARDIAC PROTECTED = No | | | |
| Air | AIRCONDITIONING = Yes | AIRCONDITIONING: hepa filtered = No | | | |
| | AIRCONDITIONING: positive pressure = No | AIRCONDITIONING: negative pressure = No | | | |
| | EXHAUST: room exhaust = No | VENTILATION = No | | | |
| Lighting | LIGHTING: colour corrected = No | LIGHTING: dimmable = No | | | |
| | LIGHTING: downlights = No | LIGHTING: downlights, dimmable = No | | | |
| | LIGHTING: fluorescent, downlights = No | LIGHTING: fluorescent, flush with ceiling, tamper proof = No | | | |
| | LIGHTING: fluorescent, general = Yes | LIGHTING: indirect = No | | | |
| Nurse Call | NURSE CALL SYSTEM = No | | | | |

Room Fabrics

| AusHFG code | Description | Comment |
|-------------|--|---|
| CLFS-006 | CEILING: plasterboard, flush set, suspended, paint, washable | |
| CLCN-002 | CORNICE: aluminium, 24mm shadow angle, powdercoat | |
| DWGL-050 | DOOR: 1600mm c/o, double leaf, fully glazed, alum/safety glass, powdercoat/paint | may be automatic, lockable |
| FLVY-007 | FLOOR FINISH: vinyl, seamless, coved, standard slip resistant | Default = vinyl, or other suitable slip resistant floor finish |
| FLGE-016 | FLOOR MAT: recessed, composite slip resistant | Optional; Attention to detailing of recessed mat to avoid trip hazard |
| FLSK-008 | SKIRTING: to suit glazing system over | |
| WLWA-004 | WALL FINISH: paint, acrylic, washable | |

Fittings, Furniture and Equipment (FF&E) Items

| AusHFG code | Description | Group | Qty | Comment |
|-------------|---|-------|-----|----------|
| FIHR-002 | BRACKET: for CCTV camera, ceiling mounted | 1 | 1 | |
| ITSE-012 | CAMERA: CCTV | 1 | 1 | optional |
| ITSE-048 | DISPLAY SCREEN: CCTV system | 3 | 1 | optional |

AHHA

autralision health infrastructure ellicore

contracte in autra ellic

Page: 1 Print Date: 20/03/2017



Room Data Sheet



Room Name

Airlock - Entry, 6m2

Room Number AIRLE-6

Engineering Services

| AusHFG code | Description | Group | Qty | Comment |
|--|--|-------|-----|---|
| ITSE-023 | DOOR RELEASE: access control, buzzer | 1 | 1 | optional |
| ELGP-101 | LGP-101 GPO: single, ceiling mounted | | 1 | |
| ELGP-101 | GPO: single, ceiling mounted | 1 | 1 | optional; for CCTV |
| ELGP-110 | GPO: single, wall mounted, cleaner | 1 | 1 | |
| ITSE-028 | INTERCOM: audiovisual, wall mounted | 1 | 1 | optional, can be integral with CCTV system. |
| ITIN-011 | OUTLET: data, single RJ45, ceiling mounted | 1 | 1 | |
| ITSE-038 READER: access control, general | | 1 | 1 | optional; swipe card access |



Page: 2 Print Date: 20/03/2017