



Room Name	Bay - Linen	Room Number BLIN			
Revision	6				
Issue Date	12.07.2023				
BRIEFING					
Briefed Area	2.00 m ²				
Hours of Operation	Up to 24 Hours				
Occupancy	accessed intermittently				
Acoustics					
Remarks					
Description / Special Requirements	The Bay - Linen is a recessed bay to a	ccommodate a clean linen supply or exchange trolley.			
	Additional Considerations:				
		d with hinged doors, sliding doors or a roller shutter where items closed. An open bay is acceptable if a covered trolley is supplied (as a control policies).			
		loors are provided, hold open hardware may be required to support alley in and out of the bay. Door protection to suit movement of beds area.			
		provided, the weight of the shutter, manual handling requirements and se shutter when opening are to be considered.			
	 If bay is enclosed, a light linen stock is accessed. 	switch or sensor may be required to provide adequate lighting when			
	 Storage for additional items such as pillows, shower curtains, privacy curtains, etc. may be provided as either joinery, a modular shelving system, a wall mounted panel with wire baskets or a mobile trolley. The storage solution will be dependent on items to be stored and if items need to be secured or covered due to infection control requirements. Inclusion of storage should consider size and manoeuvrability of the linen trolley to be used to ensure adequate clearance. 				
	instance, shelving above	height and often require a cover that is lifted from the top. In this the trolley is not recommended. If the trolley is of a suitable height is to be mounted no higher than 1800AFFL and the reach over trolley			
	 Hooks may be provided f patient's personal linen. L the trolley. 	or clean linen bags and may be differentiated for clinical, general and inen bags on hooks should be able to be accessed without moving			
		es be combined with Bay - Blanket/Fluid Warmer (see Standard itional space, FF&E and services requirements).			
SERVICES					
Electrical	BODY PROTECTED	□ CARDIAC PROTECTED □			
HVAC	AIRCONDITIONING	✓ AIRCONDITIONING: hepa filtered			
	AIRCONDITIONING: positive pressure	AIRCONDITIONING: negative pressure			
	EXHAUST: room exhaust	□ VENTILATION □			
Lighting	LIGHTING: colour corrected	LIGHTING: dimmable			
Lighting	LIGHTING: downlights	LIGHTING: downlights, dimmable			
	LIGHTING: fluorescent/LED, downlights	LIGHTING: fluorescent/LED, flush with ceiling, tamper			
	•	proof			
	LIGHTING: fluorescent/LED, general	LIGHTING: indirect			
Security / Nurse Call	NURSE CALL SYSTEM				

Room Fabrics



Page: 1 Print Date: 12/07/2023





Room Name

Bay - Linen

Room Number BLIN

AusHFG code	Description	Comment
CLTI-008	CEILING: plasterboard, drop-in tiles, prefinished, 600 x 1200	coordinated with adjacent area, flush set ceiling is also acceptable
CLCN-009	CORNICE: wall trim fixing	coordinated with adjacent area
FLVY-007	FLOOR FINISH: vinyl, seamless, coved, standard slip resistant	coordinated with adjacent area
FLSK-010	SKIRTING: vinyl, floor vinyl coved, 150H, prefinished	coordinated with adjacent area
WLWA-004	WALL FINISH: paint, acrylic, washable	
WLWA-021	WALL FINISH: vinyl, to 1800 AFFL	
WLPR-006	WALL PROTECTION: corner guards	coordinated with adjacent wall protection

Fittings, Furniture and Equipment (FF&E) Items

AusHFG code	Description	Group	Qty	Comment
FIJO-212	BULKHEAD: joinery	1	1	optional, to joinery cupboard if provided, plasterboard bulkhead is also acceptable
FIJO-129	CUPBOARD: tall, single door, adj shelves	1	1	optional, for storage of additional items such as pillows, privacy curtains, shower curtains, etc.
FIHR-029	HOOK: equipment	1	3	optional, for storage of linen bags
MMGE-109	TROLLEY: clean linen	3	1	with cover as required to suit infection prevention and control policies

Engineering Services

AusHFG code	Description	Group	Qty	Comment
ELBO-015	SWITCH: light, single	1	1	optional, lighting and controls to be coordinated with adjacent area, may be provided if bay is enclosed