

| Room Name | Bay - Meal Trolley | Room Number BMT |
|---|--|--|
| Revision | 6 | |
| Issue Date | 12.07.2023 | |
| BRIEFING | | |
| Briefed Area | 4.00 m ² | |
| Hours of Operation | Up to 24 Hours | |
| Occupancy | accessed intermittently | |
| Acoustics | | |
| Remarks | | |
| Description / Special Requirements | <p>The Bay - Meal Trolley is a recessed bay to accommodate meal trolleys during meal delivery and collection times.</p> <p><u>Additional Considerations:</u></p> <ul style="list-style-type: none"> The size and type of meal trolleys to be accommodated will be dependent on service requirements and food service models (re-thermalisation, cook fresh, cook chill, mid-meals, etc.) and will need to be confirmed to inform spatial and services requirements. Consider manoeuvrability of the meal trolley to be used to ensure adequate clearance. Most meal trolleys have 2 x fixed and 2 x swivel wheels which limit movement to position in the bay. Bay may be designed without one end wall to improve trolley access and reduce WHS risks from push/pull movements with certain types of trolleys. The Bay should be deep enough to ensure trolleys do not impede corridor circulation; minimum recommended depth is 1200mm, however, the depth may need to increase to 1500mm depending on the trolley selected. Special power may be required for re-thermalisation trolleys. | |
| SERVICES | | |
| Electrical | BODY PROTECTED <input type="checkbox"/> | CARDIAC PROTECTED <input type="checkbox"/> |
| HVAC | AIRCONDITIONING <input checked="" type="checkbox"/> | AIRCONDITIONING: hepa filtered <input type="checkbox"/> |
| | AIRCONDITIONING: positive pressure <input type="checkbox"/> | AIRCONDITIONING: negative pressure <input type="checkbox"/> |
| | EXHAUST: room exhaust <input type="checkbox"/> | VENTILATION <input type="checkbox"/> |
| Lighting | LIGHTING: colour corrected <input type="checkbox"/> | LIGHTING: dimmable <input type="checkbox"/> |
| | LIGHTING: downlights <input type="checkbox"/> | LIGHTING: downlights, dimmable <input type="checkbox"/> |
| | LIGHTING: fluorescent/LED, downlights <input type="checkbox"/> | LIGHTING: fluorescent/LED, flush with ceiling, tamper proof <input type="checkbox"/> |
| | LIGHTING: fluorescent/LED, general <input checked="" type="checkbox"/> | LIGHTING: indirect <input type="checkbox"/> |
| Security / Nurse Call | NURSE CALL SYSTEM <input type="checkbox"/> | |

Room Fabrics

| AusHFG code | Description | Comment |
|-------------|---|--|
| CLTI-008 | CEILING: plasterboard, drop-in tiles, prefinished, 600 x 1200 | coordinated with adjacent area, flush set ceiling is also acceptable |
| CLCN-009 | CORNICE: wall trim fixing | coordinated with adjacent area |
| FLVY-007 | FLOOR FINISH: vinyl, seamless, coved, standard slip resistant | coordinated with adjacent area |
| FLSK-010 | SKIRTING: vinyl, floor vinyl coved, 150H, prefinished | coordinated with adjacent area |
| WLWA-004 | WALL FINISH: paint, acrylic, washable | |
| WLWA-021 | WALL FINISH: vinyl, to 1800 AFFL | |
| WLPR-006 | WALL PROTECTION: corner guards | coordinated with adjacent wall protection |

Room Name | **Bay - Meal Trolley**
Room Number BMT
Fittings, Furniture and Equipment (FF&E) Items

| AusHFG code | Description | Group | Qty | Comment |
|-------------|----------------------------------|-------|-----|---|
| FQCA-082 | TROLLEY: food delivery, hot/cold | 3 | 2 | type of meal trolley will be dependent on food service delivery model |

Engineering Services

| AusHFG code | Description | Group | Qty | Comment |
|-------------|---------------------------|-------|-----|--|
| ELGP-109 | GPO: single, wall mounted | 1 | 2 | power requirements will be dependent on type of meal trolley |
| ELGP-140 | GPO: three phase, single | 1 | 2 | optional, power requirements will be dependent on type of meal trolley |