

| Room Name | Office - 1 Person, 12m2 | Room Number OFF-1P-12 | | | | |
|---------------------------------------|--|---|--|--|--|--|
| Revision | 6 | | | | | |
| Issue Date | 24.06.2022 | | | | | |
| BRIEFING | | | | | | |
| Briefed Area | 12.00 m ² | | | | | |
| Hours of Operation | 8am to 6pm, daily | | | | | |
| Occupancy | 1 staff, up to 3 visitors | | | | | |
| Acoustics | Sound attenuation level medium, A | Acoustic privacy is required. | | | | |
| Remarks | | | | | | |
| Description / Special Requirements | An office to accommodate 1 staff member carrying out computer based and/or administrative tasks in privacy. The room size allows for a small meeting table within the room for meetings or interviews with visitors (including staff, patients or family) as required. | | | | | |
| | Additional Considerations: | | | | | |
| | Consider placement of power and data to support flexible arrangement of the layout to suit user requirements. | | | | | |
| | Workstation length t policies. | o service requirements and local WHS/office accommodation | | | | |
| | An external outlook | is desirable. | | | | |
| SERVICES | | | | | | |
| SERVICES | | | | | | |
| Electrical | BODY PROTECTED | CARDIAC PROTECTED | | | | |
| | | | | | | |
| HVAC | AIRCONDITIONING | AIRCONDITIONING: hepa filtered | | | | |
| | AIRCONDITIONING: positive pressure | AIRCONDITIONING: negative pressure | | | | |
| | EXHAUST: room exhaust | VENTILATION | | | | |
| | | | | | | |
| Lighting | LIGHTING: colour corrected | LIGHTING: dimmable | | | | |
| | LIGHTING: downlights | LIGHTING: downlights, dimmable | | | | |
| | LIGHTING: fluorescent/LED, downlights | LIGHTING: fluorescent/LED, flush with ceiling, tamper proof | | | | |
| | LIGHTING: fluorescent/LED, general | ✓ LIGHTING: indirect | | | | |
| Security / Nurse Call | NURSE CALL SYSTEM | | | | | |

Room Fabrics

| AusHFG code | Description | Comment |
|-------------|---|----------|
| CLTI-002 | CEILING: acoustic, drop-in tiles, 600 x 1200 | |
| CLCN-009 | CORNICE: wall trim fixing | |
| DWSC-003 | DOOR: 910mm c/o, single leaf, solid core, paint | lockable |
| DWPR-001 | DOOR PROTECTION: kickplate, to 300 AFFL | |



Generated from dRofus © 2017 dRofus Pty Ltd





Room Name

Office - 1 Person, 12m2

Room Number OFF-1P-12

| AusHFG code | Description | Comment |
|-------------|---|-------------------|
| FLCP-006 | FLOOR FINISH: carpet, carpet tiles, 90/10 wool/nylon | |
| DWOB-002 | OBSERVATION: internal window, alum/glass, door height, powdercoat | with privacy film |
| FLSK-009 | SKIRTING: vinyl, feather edged, 150H, prefinished | |
| WLWA-004 | WALL FINISH: paint, acrylic, washable | |
| DWWH-005 | WINDOW | desirable |

Fittings, Furniture and Equipment (FF&E) Items

| AusHFG code | Description | Group | Qty | Comment |
|-------------|---|-------|-----|--|
| FQCW-016 | BIN: waste, general, 20L | 3 | 1 | |
| DWWD-004 | BLIND: roller | 3 | 1 | to window if provided |
| FQSN-135 | CABINET: single door, tambour, adj shelves, lockable, 1200H | 3 | 1 | lockable, size to suit service requirements |
| FQBS-018 | CHAIR: office, ergonomic | 3 | 1 | |
| FQBS-029 | CHAIR: visitor, office areas | 3 | 3 | |
| ITNE-007 | COMPUTER: desktop, with display screen | 3 | 1 | dual screens may be provided to suit service requirements |
| FIHR-026 | HOOK: coat | 1 | 2 | optional, prioritize lower hook for wheelchair users if only one hook provided |
| FQSM-007 | PEDESTAL: mobile, drawer unit, 660H | 3 | 1 | lockable |
| FQTA-057 | TABLE: round, 900 diam, work height | 3 | 1 | |
| ITNE-050 | TELEPHONE: handset, desktop, handsfree | 3 | 1 | |
| FIBM-019 | WHITEBOARD: fixed, magnetic | 2 | 1 | optional |
| FQDW-054 | WORKSTATION: straight, adj height, 1600W x 750D x 750H nom. | 3 | 1 | |

Engineering Services

| AusHFG code | Description | Group | Qty | Comment |
|-------------|---|-------|-----|--|
| ITSE-006 | BUTTON: duress, fixed | 1 | 1 | inclusion dependent on location, not required if room located in staff only area |
| ELGP-208 | GPO: double, wall mounted | 1 | 4 | extent of emergency power to be determined based on service requirements |
| ITIN-036 | OUTLET: data, triple RJ45, wall mounted | 1 | 1 | |
| ELBO-015 | SWITCH: light, single | 1 | 1 | |

Page: 2 Print Date: 29/06/2022