

Room Name	Store - Bulk	Room Number STBK
<b>Revision</b>	4	
<b>Issue Date</b>	12.07.2023	
<b>BRIEFING</b>		
<b>Briefed Area</b>	30.00 m <sup>2</sup>	
<b>Hours of Operation</b>	Up to 24 Hours	
<b>Occupancy</b>	2-3 staff, accessed intermittently	
<b>Acoustics</b>		
<b>Remarks</b>		
<b>Description / Special Requirements</b>	<p>The Store - Bulk is the primary storage area for all delivered supplies and equipment prior to distribution to hospital services / departments. The Bulk Store should be located with ready access to the loading dock area. Some departments, such as pharmacy, renal dialysis and pathology, will have bulk storage spaces that are managed independently.</p> <p><u>Additional Considerations:</u></p> <ul style="list-style-type: none"> <li>Type and extent of storage solutions for this room will depend on the departments to be serviced and operational models for stock and equipment delivery.</li> <li>Where a 'direct to imprest' model is used, consumable inventory is stored at a supply chain distribution centre and delivered to the hospital already packed into trolleys specific to the clinical area and immediately delivered to those areas. Long term storage is not required and less area is needed near the loading dock.</li> <li>A 'central bulk store' model refers to goods being delivered to the hospital in large quantities and stored in a central bulk store. The process involves the delivery of goods on pallets, goods are then checked, unloaded, and placed in a bulk store by hospital supply staff. Consumables will then be picked and packed from the central store and delivered to clinical units and other areas as required.</li> <li>Automated or motorised equipment may be considered to assist with the safe and efficient transfer of supply trolleys throughout the healthcare facility. Where tugs and AGVs are being considered, it is important to confirm clearances, door widths and turning circles within the room, in the adjacent corridor and along path of travel to all services / departments.</li> <li>Refrigerated storage requirements to be confirmed at project level.</li> <li>Wall protection is recommended to protect wall linings and finishes from damage from impact. The height of the wall protection will be dependent on equipment and trolleys frequently moved through the space; a height range of 900mm minimum up to 1500mm is recommended depending on trolley and equipment selection.</li> <li>Hold open door hardware may be required to allow for easy movement of pallet jacks and trolleys in and out of the room.</li> <li>Controlled, staff only access is required.</li> </ul>	
<b>SERVICES</b>		
<b>Electrical</b>	BODY PROTECTED <input type="checkbox"/>	CARDIAC PROTECTED <input type="checkbox"/>
<b>HVAC</b>	AIRCONDITIONING <input checked="" type="checkbox"/>	AIRCONDITIONING: hepa filtered <input type="checkbox"/>
	AIRCONDITIONING: positive pressure <input type="checkbox"/>	AIRCONDITIONING: negative pressure <input type="checkbox"/>
	EXHAUST: room exhaust <input type="checkbox"/>	VENTILATION <input type="checkbox"/>
<b>Lighting</b>	LIGHTING: colour corrected <input type="checkbox"/>	LIGHTING: dimmable <input type="checkbox"/>
	LIGHTING: downlights <input type="checkbox"/>	LIGHTING: downlights, dimmable <input type="checkbox"/>
	LIGHTING: fluorescent/LED, downlights <input type="checkbox"/>	LIGHTING: fluorescent/LED, flush with ceiling, tamper proof <input type="checkbox"/>
	LIGHTING: fluorescent/LED, general <input checked="" type="checkbox"/>	LIGHTING: indirect <input type="checkbox"/>
<b>Security / Nurse Call</b>	NURSE CALL SYSTEM <input type="checkbox"/>	

**Room Fabrics**

**Room Name | Store - Bulk**
**Room Number STBK**

AusHFG code	Description	Comment
CLTI-008	CEILING: plasterboard, drop-in tiles, prefinished, 600 x 1200	
CLCN-009	CORNICE: wall trim fixing	
DWGL-062	DOOR: 1800mm c/o, double leaf, observation panel, solid core/glass, paint	lockable or secure staff access, hold open hardware may be required
DWPR-005	DOOR PROTECTION: protection plate to 900 AFFL	
FLVY-007	FLOOR FINISH: vinyl, seamless, coved, standard slip resistant	
FLSK-010	SKIRTING: vinyl, floor vinyl coved, 150H, prefinished	
WLWA-004	WALL FINISH: paint, acrylic, washable	
WLWA-020	WALL FINISH: vinyl, to 1500 AFFL	height dependent on movement of trolleys and pallets, crash rails are also acceptable

**Fittings, Furniture and Equipment (FF&E) Items**

AusHFG code	Description	Group	Qty	Comment
FQCA-026	FRIDGE: commercial, floor standing, double door	3	1	optional
FQSN-086	SHELVING: floor standing, 900W x 400D x 2100H nom., metal	3	2	type and extent of storage solutions will be dependent on service requirements
FQSM-032	TROLLEY: receiving	3	3	

**Engineering Services**

AusHFG code	Description	Group	Qty	Comment
ELGP-208	GPO: double, wall mounted	1	1	
ELGP-223	GPO: emergency power, double, wall mounted	1	1	optional, to refrigerator if provided
ITIN-026	OUTLET: data, double RJ45, wall mounted	1	1	optional, to refrigerator if provided and temperature monitoring is required
ITIN-026	OUTLET: data, double RJ45, wall mounted	1	1	
ITSE-038	READER: access control, general	1	1	