

Room Name	Store - General		Room Number STGN	
Revision	6			
Issue Date	28.06.2021			
BRIEFING				
Briefed Area	9.00 m ²			
Hours of Operation	Available 24 hours			
Occupancy	1-2 staff, intermittently			
Acoustics	, ,			
Remarks				
Description / Special Requirements	A secure room for the storage of gener	al sup	plies used within the department.	
	Additional Design Considerations:			
	Facilities to support resto	ckina	workflows, including the use of barcode systems, to be	
	considered to suit operati	onal r	eauirements.	
	considered to suit operati	onal r	·	as
	considered to suit operati Minimum and maximum suell as fire safety require	onal r shelvir	equirements. ng heights to suit local WHS and infection control policies, a (e.g. the top of stored products is to be no nearer than 500	as Omi
	considered to suit operati Minimum and maximum s	onal r shelvir	ng heights to suit local WHS and infection control policies, a	as Omi
SEDVICES	considered to suit operati Minimum and maximum suell as fire safety require	onal r shelvir	ng heights to suit local WHS and infection control policies, a	as Omr
SERVICES	considered to suit operation Minimum and maximum sull as fire safety require to sprinkler deflectors).	onal r shelvii ments	ng heights to suit local WHS and infection control policies, a (e.g. the top of stored products is to be no nearer than 500	as Omr
SERVICES Electrical	considered to suit operati Minimum and maximum suell as fire safety require	onal r shelvir	ng heights to suit local WHS and infection control policies, a	as Omr
Electrical	considered to suit operation of the considered to suit operation of the considered to suit operation of the considered to sprinkler deflectors). BODY PROTECTED	onal r shelvii ments	ng heights to suit local WHS and infection control policies, a (e.g. the top of stored products is to be no nearer than 500 CARDIAC PROTECTED	as Omr
	considered to suit operation Minimum and maximum so well as fire safety require to sprinkler deflectors). BODY PROTECTED AIRCONDITIONING	onal r	ng heights to suit local WHS and infection control policies, a (e.g. the top of stored products is to be no nearer than 500 CARDIAC PROTECTED AIRCONDITIONING: hepa filtered	as Omi
Electrical	considered to suit operation of the considered to suit operation of the considered to suit operation of the considered to sprinkler deflectors). BODY PROTECTED	onal r	ng heights to suit local WHS and infection control policies, a (e.g. the top of stored products is to be no nearer than 500 CARDIAC PROTECTED	as Omi
Electrical	considered to suit operation Minimum and maximum so well as fire safety require to sprinkler deflectors). BODY PROTECTED AIRCONDITIONING AIRCONDITIONING: positive pressure EXHAUST: room exhaust	onal r	ng heights to suit local WHS and infection control policies, a (e.g. the top of stored products is to be no nearer than 500 CARDIAC PROTECTED AIRCONDITIONING: hepa filtered AIRCONDITIONING: negative pressure VENTILATION	as Omi
Electrical	considered to suit operation Minimum and maximum so well as fire safety require to sprinkler deflectors). BODY PROTECTED AIRCONDITIONING AIRCONDITIONING: positive pressure EXHAUST: room exhaust LIGHTING: colour corrected	onal r	ng heights to suit local WHS and infection control policies, a (e.g. the top of stored products is to be no nearer than 500 CARDIAC PROTECTED AIRCONDITIONING: hepa filtered AIRCONDITIONING: negative pressure VENTILATION LIGHTING: dimmable	as Omr
Electrical	considered to suit operation Minimum and maximum so well as fire safety require to sprinkler deflectors). BODY PROTECTED AIRCONDITIONING AIRCONDITIONING: positive pressure EXHAUST: room exhaust	onal r	ng heights to suit local WHS and infection control policies, a (e.g. the top of stored products is to be no nearer than 500 CARDIAC PROTECTED AIRCONDITIONING: hepa filtered AIRCONDITIONING: negative pressure VENTILATION LIGHTING: dimmable LIGHTING: downlights, dimmable	as Omi
Electrical	considered to suit operation Minimum and maximum so well as fire safety require to sprinkler deflectors). BODY PROTECTED AIRCONDITIONING AIRCONDITIONING: positive pressure EXHAUST: room exhaust LIGHTING: colour corrected	onal r	cardiac products is to be no nearer than 500 ce.g. the top of stored products is to be no near	as Omi
Electrical	considered to suit operation Minimum and maximum so well as fire safety require to sprinkler deflectors). BODY PROTECTED AIRCONDITIONING AIRCONDITIONING: positive pressure EXHAUST: room exhaust LIGHTING: colour corrected LIGHTING: downlights	onal r	ng heights to suit local WHS and infection control policies, a (e.g. the top of stored products is to be no nearer than 500 CARDIAC PROTECTED AIRCONDITIONING: hepa filtered AIRCONDITIONING: negative pressure VENTILATION LIGHTING: dimmable LIGHTING: downlights, dimmable	as Omi

Room Fabrics

AusHFG code	Description	Comment
CLTI-008	CEILING: plasterboard, drop-in tiles, prefinished, 600 x 1200	
CLCN-009	CORNICE: wall trim fixing	
DWGL-005	DOOR: 910mm c/o, single leaf, observation panel, solid core/glass, paint	
DWPR-005	DOOR PROTECTION: protection plate to 900 AFFL	
FLVY-007	FLOOR FINISH: vinyl, seamless, coved, standard slip resistant	
FLSK-010	SKIRTING: vinyl, floor vinyl coved, 150H, prefinished	
WLWA-004	WALL FINISH: paint, acrylic, washable	

Fittings, Furniture and Equipment (FF&E) Items

AusHFG code	Description	Group	Qty	Comment
FQSN-007	BIN: storage bins, wire mesh, stainless steel	1	15	optional
FIHR-033	PANEL: for storage bins, wall mount	1	3	optional





RDS Templates



Room Name

Store - General

Room Number STGN

AusHFG code	Description	Group	Qty	Comment
FQSN-082	SHELVING: floor standing, 900W x 450D x 2100H nom., wire	3	6	adjustable shelving; type and quantity of storage options to be determined based on service requirements
FIBM-019	WHITEBOARD: fixed, magnetic	2	1	optional

Engineering Services

AusHFG code	Description	Group	Qty	Comment
ELGP-208	GPO: double, wall mounted	1	1	
ELBO-015	SWITCH: light, single	1	1	

